IN THE CLAIMS:

1. (Currently Amended) A method for delivering content to a mobile device,

comprising the steps of:

receiving a first request for content from the mobile device;

responsive to the first request for content, sending to the mobile device an address of the

requested content in a reference format;

receiving a second request from the mobile device for the content subsequent to the first

request for content, the second request received from the mobile device being different from

the first request received from the mobile device, the second request specifying an address of

the requested content and a type of the mobile device;

responsive only to the second request, fetching the requested content in the reference

format from the specified address and converting the fetched content from the reference format

to a format suitable to the mobile device, and

delivering the converted content to the mobile device.

2. (Original) The method of claim 1, wherein the first receiving step and the

sending step are carried out by a first server and wherein the second receiving step and the

fetching and converting steps are carried out by a second server.

3. (Original) The method of claim 2, wherein the second server is a software

module.

4. (Original) The method of claim 2, wherein the software module runs on the first

server.

- 5. (Original) The method of claim 2, wherein the software module runs on at least one third server that is distinct form the first server.
 - 6. (Original) The method of claim 2, wherein the second server includes hardware.
- 7. (Original) The method of claim 1, wherein the first sending step sends the address of the requested content within a base file.
- 8. (Original) The method of claim 1, wherein the address includes a Universal Resource Locator (URL) of the requested content.
- 9. (Previously Presented) The method of claim 1, wherein the converting step carries out at least one of the following steps:

re-sizing the requested content;

converting the requested content from color to black and white;

cropping the requested content;

dithering the requested content,

flipping the requested content, and

changing a number of colors of the requested content.

- 10. (Original) The method of claim 1, further comprising a step of storing a copy of the converted content in a cache memory.
- 11. (Original) The method of claim 10, wherein the delivering step delivers the copy of the converted content from the cache memory if a valid copy of the converted content is present in the cache memory.

12. (Original) The method of claim 1, wherein the type of mobile device includes

make and model information of the mobile device.

13. (Original) The method of claim 2, wherein the second server stores a

configuration table associating the type of mobile device with display characteristics of the

mobile device.

14. (Original) The method of claim 13, wherein the converting step includes a step of

accessing the configuration table and converting the requested content to the format specified by

the display characteristics associated with the type of the mobile device.

15. (Original) The method of claim 1, wherein the requested content includes an

image and wherein the converting step includes a step of changing the resolution of the image.

16. (Original) The method of claim 1, wherein the delivering step delivers the

converted content to the mobile device at a selectable bit rate.

17. (Original) The method of claim 13, wherein the content is of a type selected from

a group including image, video, audio, audio stream and video stream.

18. (Original) The method of claim 17, wherein the reference format is different for

each type of content.

19. (Original) The method of claim 2, wherein the second server is a software

module and wherein the address of the content in the reference format is passed as an argument

to the software module.

20. (Currently Amended) A computer system configured to deliver content to a

mobile device, comprising:

a first server configured to deliver, responsive to a first request for content from the

mobile device, an address of a content in a reference format responsive to a request for the

content from the mobile device, and

a first proxy server configured to receive a second request from the mobile device for the

content, the second request received from the mobile device being different from the first

request received from the mobile device, the second request including the address of the

requested content in the reference format and a type of the mobile device, to fetch the content at

the received address responsive only the second request only, to convert the fetched content

from the reference format to a format suitable to the type of mobile device and to deliver the

converted content to the mobile device.

21. (Original) The computer system of claim 20, wherein the first proxy server is a

software module.

22. (Original) The computer system of claim 21, wherein the software module runs

on the first server.

23. (Original) The computer system of claim 21, wherein the software module runs

on at least one third server that is distinct form the first server.

24. (Previously Presented) The computer system of claim 20, wherein the first proxy

server includes hardware.

25. (Original) The computer system of claim 24, wherein the first server and the first

proxy server are coupled to one another by a computer network.

26. (Previously Presented) The computer system of claim 25, further including a

plurality of second proxy servers each of the plurality of second proxy servers being configured

as first proxy servers and being coupled to a computer network.

27. (Original) The computer system of claim 26, wherein at least some of the

plurality of second proxy servers are geographically separated from one another.

28. (Original) The computer system of claim 20, wherein the first server is

configured to send the address of the requested content within a base file.

29. (Original) The computer system of claim 20, wherein the address includes a

Universal Resource Locator (URL) of the requested content.

30. (Previously Presented) The computer system of claim 20, wherein the first proxy

server is also configured to selectively re-size the requested content, convert the requested

content from color to black and white, crop the requested content, dither the requested content,

flip the requested content or to change a number of colors of the requested content.

31. (Original) The computer system of claim 20, wherein the first proxy server is

also configured to store a copy of the converted content in a cache memory.

32. (Original) The computer system of claim 31, wherein the first proxy server is

configured to deliver the copy of the converted content from the cache memory if a valid copy of

the converted content is present in the cache memory.

33. (Original) The computer system of claim 20, wherein the type of mobile device includes make and model information of the mobile device.

34. (Original) The computer system of claim 20, wherein the first proxy server is configured to maintain a configuration table associating the type of mobile device with display characteristics of the mobile device.

35. (Original) The computer system of claim 34, wherein the first proxy server is further configured to access the configuration table and convert the requested content to the format specified by the display characteristics associated with the type of the mobile device.

36. (Original) The computer system of claim 20, wherein the content is of a type selected from a group including image, video, audio, audio stream and video stream.

37. (Original) The computer system of claim 36, wherein the reference format is different for each type of content.

38. (Original) The computer system of claim 20, wherein the first proxy server is a software module and wherein the address of the content in the reference format is passed as an argument to the software module.